

The brand new Crimper SC 05

Z+F presents the new electro-pneumatic Crimper SC 05. With this new machine insulated and uninsulated ferrules from 0.34 mm² to 4 mm² and ferrule length from 6 to 18 mm can be processed. To switch the processed cross section you only have to change the feeding funnel. No further tool changes are required. The SC 05 is equipped with a quadro-crimping-tool.

The new Stripper-Crimper AM 02 universal

The new compact Stripper-Crimper with quadro-crimping-tool based on the AM 02 can process ferrules from 0.5 to 2.5 mm² in the ferrule length 6 to 12 mm. For cross section changing only the ferrule holder and feeding bowl has to be changed. The AM 02 is very user friendly due to the tried and tested touchscreen display known from the UNIC-series. The very short cycle time of only 1.5 seconds saves time and money.

Improved Crimper-LS

The improved Crimper-LS replaces the current version of the Crimper-L and -LS. The improved version for insulated Z+F ferrules comes with a wider crimping range of 0.34 mm² to 4 mm² and ferrule length from 6 to 12 mm as well as a shorter cycle time of only 1 second. Like the SC 05 and the AM 02 universal the new Crimper-LS comes with a quadro-crimping-tool. A touchscreen display makes the Crimper-LS straight forward to use.

Z+F Crimpforce monitoring CK01

With the crimpforce monitoring CK01 Z+F accommodates to the increasing requirements for quality, reliability and verifiability, especially in automotive and aeronautical sector - but also in other security relevant divisions. With this new developed crimpforce monitoring for our Z+F machines it is possible to observe the force, the quality of the crimp within given tolerances and to keep records of this crimping process. The software "crimpforce manager" is a complete tool for visualization, parameterization and documentation of the crimping process on your PC.



Contact

Zoller + Fröhlich GmbH
Simoniusstrasse 22
88239 Wangen im Allgäu
Germany

Phone: +49 7522 9308-0
Fax: +49 7522 9308-252
info@zofre.de
www.zofre.de